

# ARIZONA TILE

# AEQUA SERIES



Aequa Nix



Aequa Castor



Hex 2-1/2 Mesh



Aequa Cirrus



Hex 2-1/2 Mesh



Aequa Nix



Hex 2-1/2 Mesh



Aequa Silva



Hex 2-1/2 Mesh



Aequa Tur



Hex 2-1/2 Mesh

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



For packaging information, please contact your local Arizona Tile.

**DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.**

Please view actual material when making your selection, as the images on this page are only representative.

Revised 04/29/25

## MADE IN ITALY

### PRODUCT TYPE

Rectified Color Body Porcelain

†Glazed Porcelain

Digital Print Technology

### STOCKED COLORS

Aequa Castor

Aequa Cirrus

Aequa Nix

Aequa Silva

Aequa Tur

### STOCKED SIZES

8 × 32

\*8 × 32 R11 Anti-Slip Finish

12 × 48

†\*16 × 48 × 2cm Paver

R11 Anti-Slip Finish

Hex 2-1/2 × 2-1/2

### STOCKED TRIM

4 × 32 SBN

\*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit [www.arizonatile.com](http://www.arizonatile.com)

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip finish. To be certified as R11 Anti-Slip Finish, a tile must pass internationally-recognized testing.

The Aequa Series is a rectified color body porcelain that is available in two finishes, including the R11 Anti-Slip Finish. Giving the appearance of a reclaimed wood, this series provides the warmth of timeworn matter that has taken on new colors and nuances over time. Because this material is a porcelain product, minimal maintenance is required. The 8 × 32 and 16 × 48 × 2cm Paver sizes are available in R11 Anti-Slip finish, which is ideal for exterior applications. All sizes and finishes are available in five colors. Please note, for pavers, a minimum grout spacing of 1/8" or 3mm is recommended.

Piece to piece variation in shade or color is inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications.

For proper bonding, medium bed mortar should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

### RECOMMENDED USES

Commercial

Residential

Interior Floor

\*Exterior Floor

Interior Wall

Exterior Cladding

Fireplaces

Shower Walls

Steam Showers

\*\*Shower Floors

Pool & Spa

\*8 × 32 R11 Anti-Slip Finish Only

\*\*Hex 2-1/2 Mesh and 8 × 32 R11 Anti-Slip Finish Only

### PAVER RECOMMENDED USES

†Commercial

†Residential

†Exterior Floor

### SPECIAL ORDER

Special Order Sizes and Finishes Available: Please contact your Sales Representative for more details.

**DYNAMIC C.O.F. WET: ≥0.42**

**P.E.I. RATING: 4**

**FROSTPROOF: Yes**