

# NEW PRODUCT SERIES

## Technical Information Spec-sheet

SERIES NAME

### TECHNICAL CHARACTERISTICS

Available Formats:	8x48		
Style Description:	Wood	Glaze Application Method:	Inkjet
Visual Characteristics:	Wood	Number of Faces/Screens:	8
Thickness in mm:	9mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential Commercial	Color Body Unglazed:	NORMAL
Recycled Content: Post or Pre Customer		Surface Type:	SATIN
Rectified or Pressed	Rectified	Recommended Grout Joint:	2 MM

### PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	2 (Natural & Blanco V3)	Dynamic COF:	.80 Dry/ .67 Wet
Scratch Hardness (MOHS)		Breaking Strength:	UNI EN ISO 10545-4
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	Yes		

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*