

# ARIZONA TILE



BA-Almond



BA-Amber



BA-Barrel



BA-Cortex



BA-Cotton



Straight Stack  
1 x 24 Mesh



Hex 16 x 18 Mesh



Straight Stack  
1 x 24 Mesh



Hex 16 x 18 Mesh



Straight Stack  
1 x 24 Mesh



Hex 16 x 18 Mesh



Straight Stack  
1 x 24 Mesh



Hex 16 x 18 Mesh



Straight Stack  
1 x 24 Mesh



Hex 16 x 18 Mesh

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



For packaging information, please contact your local Arizona Tile.

**DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.**

Please view actual material when making your selection, as the images on this page are only representative.

Revised 03/25/25

# BIO ATTITUDE SERIES

## MADE IN ITALY

### PRODUCT TYPE

Rectified Glazed Porcelain  
Digital Print Technology

### STOCKED COLORS

BA-Almond  
BA-Amber  
BA-Barrel  
BA-Cortex  
BA-Cotton

### STOCKED SIZES

8 x 48  
Straight Stack 1 x 24 Mesh  
Hex 16 x 18 Mesh

### RECOMMENDED USES

Commercial  
Residential  
Interior Floor  
Interior Wall  
Exterior Cladding  
Fireplaces  
Shower Walls  
\*Shower Floors  
Steam Showers  
Pool & Spa  
\*Straight Stack 1 x 24 Mesh and Hex 16 x 18 Mesh only

**DYNAMIC C.O.F. WET:** ≥0.42

**P.E.I. RATING:** 4

**FROSTPROOF:** Yes

The Bio Attitude series is a rectified glazed porcelain that captures the truest essence of oak, making us rediscover the rustic beauty of nature. An added benefit is that Bio Attitude features PROTECT® technology, which works continuously to eliminate up to 99.9% of bacteria. PROTECT® surfaces have been developed with Microban®, a proven antimicrobial product protection technology developed by the world leader in the sector. Integrated during the manufacturing stage, Microban® helps fight the growth of degrading bacteria on the surface of the tile for its expected lifetime. The result is a surface that stays cleaner and fresher in between cleans. It is also inherently more durable and unalterable by climate conditions. Because this material is a porcelain product, minimal maintenance is required. This series is suitable for residential and commercial applications.

There can be noticeable variance between pieces, so it is important and recommended that a range of this product be viewed before finalizing a purchase. Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected.

For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

**PRODUCT CONTAINS  
≥40% PRE-CONSUMER  
RECYCLED CONTENT**