

CASABLANCA blurs the lines between classic and contemporary, with vibrant colorways, go-to shapes and fun patterns. Bring dimension to walls with the structured wall tile, and round out the design with the petite hexagon floor tile.

THE DETAILS:

- · 2" x 6" double-fired, dimensional wall tiles in three pre-mixed profiles
- 5.5" x 6" hexagonal floor tiles in solid colorways and complimenting decors

STYLE IT:

- · Bar backsplashes with exposed shelving
- Mixed hexagon solid and decors in a powder or smaller bathroom floor
- Lobby or activity room accent walls in boutique hotels





Photo features Saffron 2" x 6"





CASABLANCA

Extruded Wall and Porcelain Floor Tile



COLOR AVAILABILITY - WALL



COLOR AVAILABILITY - FLOOR



SIZE AVAILABILITY

NOMINAL SIZE	ACTUAL SIZE	THICKNESS	PC/CARTON	SQ.FT/CARTON
2" × 6"*	1.97" x 5.91"	8mm - 12mm	66	5.35
5.5" x 6"	5.51" x 6.34"	3/8"	30	5.37

^{*}All three profiles are included in equal quantities in each carton.

CASABLANCA

Extruded Wall and Porcelain Floor Tile



TECHNICAL SPECIFICATIONS		WALL	FLOOR
=	Material Type	Ceramic (Extruded)	Porcelain
	Finish	Glossy	Matte
	Edge	Pressed	Pressed
**	Color Variation	V4	V3
	Printing	N/A	Digital
<u> </u>	Installation	Wall	Wall / Floor
	Usage	Residential / Commercial	Residential / Commercial
	Grout Joint Recomm.	1/16" or No Grout Joint	1/8"
▶ ∢	Thickness	8mm - 12mm	3/8"
444	Shower Pan	No	Yes
<u></u>	Pool Lining*	No	Yes
•	Fireplace Surround*	Yes	Yes
*	Frost Resistant	No	Yes

^{*}Proper installation methods must be followed per project. Please reference TCNA for more information.

TEST RESULTS		WALL	FLOOR
***	Water Absorption (C373)	> 10%	≤ 0.5 %
-=	Breaking Strength (C648)	N/A	≥ 250 LBS
₩	Surface Abrasion (MOHS)	N/A	5.0
F	Chem. Resistance (C650)	N/A	Resistant
4	D.C.O.F. (A137.1)	N/A	> 0.42
P	Scratch Hardness (P.E.I)	N/A	4

Special Considerations for Wall:

- Variations in caliber, flatness, straightness, texture, design and shade are present in the artisanal manufacture process of this product.
- Special and vibrant glazes can produce an intentional crackle upon production, in transport or after installation.
- Dry-stacking is recommended for wall tile, although not required. When installing in a wet area, a waterproof membrane is required prior to installation, and grouting and sealing will be necessary.

