



TERRAZZO LOOK

MODERNIST™
COLORBODY™ PORCELAIN

MODERNIST™

COLORBODY™ PORCELAIN

A Modern Return to Mid-Century Appeal

Modernist™ offers the retro look of terrazzo inspired by a mid-century design aesthetic. This collection's dynamic matte surface and subtle flecked look bring exciting dimension to the surface. A time-honored visual offers ease and style, sure to make a statement with surrounding décor and accents.

TERRAZZO LOOK

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER
FLOOR



EXTERIOR
FLOOR



STEPWISE™



TRU-EDGE™



MADE IN
THE U.S.A.



LARGE
FORMAT



MOSAIC/
DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



PC
COLORBODY™
PORCELAIN

LOW HIGH

NOT APPLICABLE
FOR ALL PRODUCTS
IN THIS SERIES. SEE
CHARTS FOR FULL
PRODUCT DETAILS.

SPECIAL FEATURES

Cover photo features Modernist™ Soriano Clay 24 x 24 on the floor.
Above photo features Modernist™ Pearsall Grey 24 x 24 on the floor.

SIZES:



36 x 36
Floor Tile



24 x 24
Floor Tile

FINISHES: MATTE

COLOR PALETTE



BERTOIA
WHITE




PEARSALL
GREY



SORIANO
CLAY



PROUVÉ
STEEL



KNOLL
CHARCOAL

FLOOR TILE



BERTOIA WHITE MD85



PEARSALL GREY MD86



SORIANO CLAY MD87



PROUVÉ STEEL MD88



KNOLL CHARCOAL MD89



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



CLIMATEPRO™



SIMPLICLEAN™

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	36 x 36 Floor Tile	(35-3/8" x 35-3/8") (89.80 cm x 89.80 cm)	3/8"	17.36	2
	24 x 24 Floor Tile	(23-9/16" x 23-9/16") (59.80 cm x 59.80 cm)	3/8"	11.55	3

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

TRIM

Type	Number	Size	Pieces/ Carton
 Bullnose	P43F9	3 x 24	10

INSTALLATION

Grout Joint Recommendation	Shade Variation
----------------------------	-----------------

1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)



Medium (V2)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltille.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltille.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltille.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltille.com.

