NEW PRODUCT SERIES

Technical Information Spec-sheet

International Wholesale Tile, LLC

SERIES NAME	**BOREALIS**

TECHNICAL CHARACTERISTICS			
Available Formats:	12X71		
Style Description:	Wood	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	48
Thickness in mm:	10.5	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	40%	Surface Type:	Matte
Rectified:	Yes	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION			
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)			
Water Absorption:	0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	>0.42
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	N/A
PEI/Abrasion Resistance:	5	Deep Abrasion Test <175mm^2:	Yes
Chemical Resistance:			

PACKING INFORMATION - ***Please inquire with Customer Service for additional sizes***			
SqFt per Carton:	11.62	Pieces per Carton:	2
SqFt per Pallet:	418.32	Pounds per Carton:	
Boxes per Pallet:	36	SqFt per Container:	
Pallets per Container:	17		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.

3500 SW 42nd Avenue | Palm City, FL 34990 | T: 800-340-TILE (8453) | F: 888-765-TILE (8453)
info@iwttesoro.com | www.iwttesoro.com