NEW PRODUCT SERIES

Technical Information Spec-sheet

IWT TESORO Quality Products for Life

INTERNATIONAL WHOLESALE TILE, LLC

SERIES NAME	**Walk**

TECHNICAL CHARACTERISTICS			
Available Formats:	12x24, 24x48, 24x48 Deco, Oval mosaic		
Style Description:	Stone	Glaze Application Method:	Inkjet
Thickness in mm:	8mm 12x24, 9.5mm 24x48	Number of Faces/Screens:	36 12x24, 9 24x48
Modular Suitability:	No	Number of Punches/Molds:	1
Application:	Residential • Wall wet/dry • Interior floor dry • Interior floor wet (mosaic) • Exterior wall Commercial • Wall wet/dry • Exterior wall	Body Type:	Porcelain
Rectified or Pressed:	Rectified	Color Body:	No
Recycled Content: Post or Pre Customer	20%	Surface Type:	Flat matte
		Recommended Grout Joint:	≥2mm

PRODUCT TESTING INFORMATION			
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)			
Water Absorption:	<.5%	Chemical Resistance:	GA, LA, HA
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	≥.42
Scratch Hardness (MOHS)	7	Breaking Strength:	35N/mm^2
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm^2:	Glazed porcelain

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.

3500 SW 42nd Avenue | Palm City, FL 34990 | T: 800-340-TILE (8453) | F: 888-765-TILE (8453)
info@iwttesoro.com | www.iwttesoro.com