

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

PUKKA

TECHNICAL CHARACTERISTICS

Available Formats:	2.5X10		
Style Description:	Painted Brick	Glaze Application Method:	Spray/Bell
Thickness in mm:	8.3	Number of Faces/Screens:	Infinite
Application:	-Wall Dry Interior only -Wall Wet Interior only (Must be sealed before grouting if wet area)	Number of Punches/Molds:	Infinite
Rectified or Pressed:	Pressed	Body Type:	Ceramic
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Undulated/Irregular/Relief
		Recommended Grout Joint:	3mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	>10%	Chemical Resistance:	GBL
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	N/A
Frost Resistant:	No	Breaking Strength:	N/A
PEI/Abrasion Resistance:	N/A	Thermal Shock Resistance:	N/A

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.