



Light
100008622 - 12"x24" Field Tile - Honed
100008625 - 12"x24" Field Tile - Lappato



Light
100008715 - 24"x24" Field Tile - Honed
100008718 - 24"x24" Field Tile - Lappato



Light
100008628 - 24"x48" Field Tile - Honed
100008631 - 24"x48" Field Tile - Lappato



Light
100008721 - 4"x4" Mosaic - Honed
(12"x12" Sheet)



Walnut
100008623 - 12"x24" Field Tile - Honed
100008626 - 12"x24" Field Tile - Lappato



Walnut
100008716 - 24"x24" Field Tile - Honed
100008719 - 24"x24" Field Tile - Lappato



Walnut
100008629 - 24"x48" Field Tile - Honed
100008632 - 24"x48" Field Tile - Lappato



Walnut
100008722 - 4"x4" Mosaic - Honed
(12"x12" Sheet)



Grey
100008621 - 12"x24" Field Tile - Honed
100008624 - 12"x24" Field Tile - Lappato



Grey
100008714 - 24"x24" Field Tile - Honed
100008717 - 24"x24" Field Tile - Lappato



Grey
100008621 - 24"x48" Field Tile - Honed
100008630 - 24"x48" Field Tile - Lappato



Grey
100008720 - 4"x4" Mosaic - Honed
(12"x12" Sheet)

Detail View of Finishes



Honed



Lappato



Ikonite

Glazed Color Body Porcelain

Photo Features 12"x24" Field Tile on Wall and 24"x48" Field Tile on Floor- Honed in Walnut.


SIZING & PACKAGING

Type	Shape	Light Item Code	Walnut Item Code	Grey Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Porcelain		100008622	100008623	100008621	12"x24"	Rectified Field Tile - Honed	8	15.50
		100008625	100008626	100008624	12"x24"	Rectified Field Tile - Lappato	8	15.50
		100008715*	100008716*	100008714*	24"x24"	Rectified Field Tile - Honed	4	15.50
		100008718*	100008719*	100008717*	24"x24"	Rectified Field Tile - Lappato	4	15.50
		100008628	100008629	100008627	24"x48"	Rectified Field Tile - Honed	2	15.50
		100008631	100008632	100008630	24"x48"	Rectified Field Tile - Lappato	2	15.50
Mosaic		100008721	100008722	100008720	(12"x12" Sheet)	4"x4" Mosaic - Honed	5	-

ANSI TECHNICAL SPECIFICATIONS


	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	-	Unaffected	7	> 250 lbf	≤ 0.5%	Unaffected

Shade Variation




APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	●	◻	◻	●	◻	◻
Commercial	●	◻	◻	●	◻	◻



LEGEND

- ◻ Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ◻ Applications & ANSI Technical Specifications do not apply
- * Special Order only



Use of a leveling system during installation is strongly recommended

IMPORTANT: Installation Instructions - We recommend wet cutting or the score and snap method during the installation process. Improper installation techniques could expose installer to inhalation of harmful silica dust. Do not dry cut product using power tools during the installation process. Using dry cutting methods could present a risk of acute lung injury. If adequate ventilation cannot be achieved, wear a mask or respirator. For more information, see the SDS at www.bedrosians.com/en/installation-care-maintenance/.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Porcelain, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

