

ARIZONA TILE

SHEN SERIES



Shen Graylake



PRODUCT TYPE

Rectified Color Body Porcelain
Digital Print Technology

STOCKED COLORS

Shen Balance Grey
Shen Essence
Shen Graylake
Shen White Shades

RECOMMENDED USES

Commercial
Residential
Interior Floor
Interior Wall
Exterior Cladding
Fireplaces
Shower Wall
*Shower Floors
Steam Showers
Pool & Spa

*2 x 2 Mosaic Mesh Only

STOCKED SIZES

12 x 24
24 x 48
*2 x 2 Mosaic Mesh

*Tiles are randomly placed on mesh.

DYNAMIC C.O.F. WET: ≥ 0.42

P.E.I. RATING: 4

FROSTPROOF: Yes

SPECIAL ORDER

Special Order Sizes, Colors Available: Please contact your Sales Representative for more details.

STOCKED TRIM

3 x 12 SBN



Shen Balance Grey



2 x 2 Mosaic Mesh



Shen Essence



2 x 2 Mosaic Mesh



Shen Graylake



2 x 2 Mosaic Mesh



Shen White Shades




2 x 2 Mosaic Mesh

The Shen series is an American-made porcelain tile. It masterfully mimics the look of wood with monochromatic tones that evoke the serene essence of stained wood. Perfect for those who seek to infuse their surroundings with a subtle touch of nature. Because this material is a porcelain product, minimal maintenance is required.

There can be noticeable variances between pieces, so it is important and recommended that a range of this product be viewed before finalizing a purchase. Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. This series is suitable for residential and commercial projects.

For proper bonding, LHT/LFT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required. This series is suitable for residential and commercial applications.

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



**PRODUCT CONTAINS
≥40% PRE-CONSUMER
RECYCLED CONTENT**

For packaging information, please contact your local Arizona Tile.

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Please view actual material when making your selection, as the images on this page are only representative.

Revised 09/23/25

www.arizonatile.com