Be Open

PHILADELPHIA COMMERCIAL


100 Spirit


300 Truth


400 Honor


410 Compassion


500 Power


505 Courage


515 Genuine


700 Purpose


705 Strength


710 Self


800 Faith


510 Wisdom

For reference purposes only if printed or downloaded.

Be Open

Style Name	**Be Open**
Collection Name	**Embrace The Moment**
Style Number	**54807**
Product Type	**Soft Surface - Philadelphia**
Construction	**Pattern Loop**
Fiber	**EcoSolution Q® Nylon**
Dye Method	**Solution Dyed**
Primary Backing	**Synthetic**
Secondary Backing	**StaLok®**
Traffic Rating	**Severe**
Protective Treatments	**SSP Protective Treatments**

	U.S.	Metric
Product Size	**12 ft**	**3.66 m**
Gauge	**1/10 in**	**39.37 per 10 cm**
Stitches	**12 per in**	**47 per 10 cm**
Finished Pile Thickness	**0.103 in**	**2.62 mm**
Average Density	**6291 oz/yd³**	
Total Thickness	**0.25 in**	**6.35 mm**
Tufted Weight	**18 oz/yd²**	**610.3 g/m²**
Pattern Repeat	**0.5 ft W X 0.29 ft L**	**15.24 cm W X 8.97 cm L**



Recommended Installation Methods

Direct Glue

Performance Testing

Pill Test	**Pass**
Radiant Panel	**Class I**
NBS Smoke	**Less than 450**
Electrostatic Propensity	**Less than 3.5 kv**
CRI® Greenlabel Plus	**GLP8472**
ADA Compliance	**>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes**

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

Broadloom Lifetime Commercial Limited Warranty with Stain and Color

Environmental

Recycled Content	**Pre-consumer - <1%, Post-consumer - 0%**
Environmental Product Declaration (EPD)	**3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804**
Health Product Declaration (HPD)	**Disclosed to 1,000 ppm**
Cradle to Cradle Certified®	**Certified Bronze Level (Version 3.1)**
NSF 140	**Conforms to the NSF/ANSI 140 - 2019 Sustainability Assessment for Carpet**
Indoor Air Quality	**CRI® Green Label Plus (GLP8472)**

For reference purposes only if printed or downloaded.