NEW PRODUCT SERIES

Technical Information Spec-sheet

International Wholesale Tile, LLC

SERIES NAME	**Memento**

TECHNICAL CHARACTERISTICS			
Available Formats:	24x48, 24x24, 12x24 2x2 Mosaic 12x12 Sheet, 3x24 Bullnose		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Marble	Number of Faces/Screens:	24x48(24), 24x24(48), 12x24(60)
Thickness in mm:	9mm / 10mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte and Polished
Rectified:	Yes	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION			
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)			
Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	3	Dynamic COF:	>0.4 Polished / >0.6 Matte
Scratch Hardness (MOHS)	>6	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	Resist
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm^2:	
Chemical Resistance:			

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*			
SqFt per Carton:	14.98	Pieces per Carton:	2
SqFt per Pallet:	449.40	Pounds per Carton:	65.163
Boxes per Pallet:	30	SqFt per Container:	13032.60
Pallets per Container:	29		

Note:
Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".

3500 SW 42nd Avenue | Palm City, FL 34990 | T: 800-340-TILE (8453) | F: 888-765-TILE (8453)
info@iwttesoro.com | www.iwttesoro.com

Modified: 03/25/2015