NEW PRODUCT SERIES

Technical Information Spec-sheet

International Wholesale Tile, LLC

SERIES NAME	PAONAZZO

TECHNICAL CHARACTERISTICS			
Available Formats:	12x24, 24x24, 36x36, 24x48, 3x24 BN, 2" Hex Mosaic, 3x3 Mosaic		
Style Description:	Calacatta Gold	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	12x24(38), 24x24(26), 36x36 (10)
Thickness in mm:	10.5 MM	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte/Glossy
Rectified:	Rectified	Recommended Grout Joint:	2.5mm

PRODUCT TESTING INFORMATION			
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)			
Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	Matte 0.42
Scratch Hardness (MOHS)		Breaking Strength:	1600-2400N
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm²:	
Chemical Resistance:			

PACKING INFORMATION - 12x24 *Please inquire with Customer Service for additional sizes*			
SqFt. Per Carton	11.63	Pieces per Carton:	6
SqFt per Pallet:	558.24	Pounds per Carton:	
Boxes per Pallet:	48	SqFt per Container:	
Pallets per Container:	25		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.

3500 SW 42nd Avenue | Palm City, FL 34990 | T: 800-340-TILE (8453) | F: 888-765-TILE (8453)
info@iwttesoro.com | www.iwttesoro.com