

ARIZONA TILE

INTENSE SERIES



Intense Beige



2 x 2 Mosaic Mesh



Mixed Straight
Stack 1 x 12 Mesh



Mixed Chevron
Mesh



Mixed 4" Hex Mesh



Intense Clair



2 x 2 Mosaic Mesh




Mixed Straight
Stack 1 x 12 Mesh



Mixed Chevron
Mesh



Mixed 4" Hex Mesh



Intense Perle



2 x 2 Mosaic Mesh



Mixed Straight
Stack 1 x 12 Mesh



Mixed Chevron
Mesh



Mixed 4" Hex Mesh



Intense Toffee



2 x 2 Mosaic Mesh



Mixed Straight
Stack 1 x 12 Mesh




Mixed Chevron
Mesh



Mixed 4" Hex Mesh

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



**PRODUCT CONTAINS
≤40%PRE-CONSUMER
RECYCLED CONTENT**

MADE IN ITALY

PRODUCT TYPE

Rectified Color Body Porcelain
Digital Print Technology

STOCKED COLORS

Intense Beige
Intense Clair
Intense Perle
Intense Toffee

STOCKED FINISHES

Matte
*R11 Finish

STOCKED SIZES

12 x 24
24 x 24
24 x 48
*24 x 48 R11 Finish
24 x 48 Trait
2 x 2 Mosaic Mesh
Mixed Chevron Mesh
Mixed Hex 4" Mesh
Mixed Straight Stack 1 x 12 Mesh

*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11, a tile must pass internationally-recognized testing.

To learn more, visit www.arizonatile.com

RECOMMENDED USES

Commercial
Residential
Interior Floor
*Exterior Floor
Interior Wall
Exterior Cladding
Fireplaces
Shower Walls
**Shower Floors
Steam Showers
Pool & Spa
*24 x 48 R11 Finish Only
**2 x 2 Mosaic Mesh, Mixed 4" Hex Mesh,
Mixed Straight Stack 1 x 12 Mesh and
24 x 48 R11 Finish Only

STOCKED TRIM

3 x 12 SBN

DYNAMIC C.O.F. WET: ≥0.42

P.E.I. RATING: 4

FROSTPROOF: Yes

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Finish.

The Outer Limits® Collection includes products designed for outdoor living, featuring slip-resistant porcelain tiles, and countertop materials ideal for outdoor kitchens and exposed environments. Please confirm which exterior surface(s) a product is recommended for in the Products section of our website.

The Intense series is an Italian made porcelain. Inspired by sedimentary limestone, this series faithfully reproduces the granules and micro-inclusions of fossils that are typical of this stone. The 24 x 48 size includes a Trait texture that recreates the effect of chiseled stone through a processing technique that uses engraving to give the entire surface a more decorative look, yet can still be used on floors. Because this material is a porcelain product, minimal maintenance is required. This series is suitable for residential and commercial application.

Intense features PROTECT® technology, which makes it easy to sanitize and eliminates up to 99.9% of bacteria. Besides being beautiful and remarkably resistant, PROTECT® surfaces have been crafted with Microban®, a proven antimicrobial product protection technology developed by the world leader in the sector. Integrated during the manufacturing stage, Microban® helps fight the growth of degrading bacteria on the surface of the tile for its expected lifetime. The result is a surface that stays cleaner and fresher in between cleans. It is also inherently more durable and unalterable by climate conditions.

When mixing sizes within a series, shade, texture and calibration differences should be expected. Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color.

For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

For packaging information, please contact your local Arizona Tile.

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Please view actual material when making your selection, as the images on this page are only representative.

Revised 03/09/26

www.arizonatile.com