



Style Name	Primus	
Style Number	54510	
Product Type	Soft Surface - Philadelphia	
Construction	Cut/Uncut	
Fiber	EcoSolution Q® Nylon	
Dye Method	Beck Dyed	
Primary Backing	Synthetic	
Secondary Backing	ClassicBac®	
Traffic Rating	Heavy	
	U.S.	Metric
Product Size	12 ft	3.66 m
Gauge	1/8 in	31.5 per 10 cm
Stitches	12 per in	47 per 10 cm
Finished Pile Thickness	0.188 in	4.78 mm
Average Density	6894 oz/yd³	
Total Thickness	0.338 in	8.59 mm
Tufted Weight	36 oz/yd²	1220.6 g/m²
Pattern Repeat	0.04 ft W X 0.17 ft L	1.27 cm W X 5.08 cm L
GSA Approved Product	Yes	



Recommended Installation Methods

Direct Glue

Performance Testing

Pill Test	Pass
Radiant Panel	Class I
NBS Smoke	Less than 450
Electrostatic Propensity	Less than 3.5 kv
ADA Compliance	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

Broadloom 10 year Commercial Limited Warranty

Environmental

Recycled Content	Pre-consumer - <1%, Post-consumer - 0%
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804
Health Product Declaration (HPD)	Disclosed to 1,000 ppm
Cradle to Cradle Certified®	Certified Silver Level (Version 3.1)
NSF 140	Conforms to the NSF/ANSI 140 - 2019 Sustainability Assessment for Carpet

Specifications are subject to nominal manufacturing variance.
Material supply and/or manufacturing processes may necessitate changes without notice.