


17300 Transistor




17301 Power House




17302 Electric




17304 Breaker




17402 Current



17500 Capacitor



17501 Adapter



17700 Terminal



17401 Direct Line

Style Name	Hot Circuit	
Style Number	54417	
Product Type	Soft Surface - Philadelphia	
Construction	Graphic Loop	
Fiber	EcoSolution Q® Nylon	
Dye Method	SOLUTION DYED/ SPACE DYED	
Primary Backing	Synthetic	
Secondary Backing	StaLok®	
Traffic Rating	Severe	
	U.S.	Metric
Product Size	12 ft	3.66 m
Gauge	1/10 in	39.37 per 10 cm
Stitches	8 per in	32 per 10 cm
Finished Pile Thickness	0.112 in	2.84 mm
Average Density	8357 oz/yd³	
Total Thickness	0.276 in	7.01 mm
Tufted Weight	26 oz/yd²	881.5 g/m²
Pattern Repeat	0.05 ft W X 0.5 ft L	1.51 cm W X 15.24 cm L
GSA Approved Product	Yes	

Recommended Installation Methods

Direct Glue

Performance Testing

Pill Test	Pass
Radiant Panel	Class I
NBS Smoke	Less than 450
Electrostatic Propensity	Less than 3.5 kv
CRI® Greenlabel Plus	GLP8472
ADA Compliance	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

Broadloom Lifetime Commercial Limited Warranty

Environmental

Recycled Content	Pre-consumer - <1%, Post-consumer - 0%
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804
Health Product Declaration (HPD)	Disclosed to 1,000 ppm
Cradle to Cradle Certified®	Certified Bronze Level (Version 3.1)
NSF 140	Conforms to the NSF/ANSI 140 - 2019 Sustainability Assessment for Carpet
Indoor Air Quality	CRI® Green Label Plus (GLP8472)

Specifications are subject to nominal manufacturing variance.
Material supply and/or manufacturing processes may necessitate changes without notice.