

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Marrakech

TECHNICAL CHARACTERISTICS

Available Formats:	4x4, 2x8		
Style Description:	Mediterranean	Glaze Application Method:	Inkjet
Thickness in mm:	9.5	Number of Faces/Screens:	4x4=150 faces 2x8=300 faces
Application:	Residential Wall/Floor, Exterior Wall, Wet Wall, Pool	Number of Punches/Molds:	8
Rectified or Pressed:		Body Type:	Porcelain
Recycled Content: Post or Pre Customer	50%	Surface Type:	Undulated
		Recommended Grout Joint:	3mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	≤ 0.5%	Chemical Resistance:	LA-HA
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	>0.42 Matte Finish Only
Frost Resistant:	Yes	Breaking Strength:	≤ 700 N
PEI/Abrasion Resistance:	5:White, Total White, Ivory 4:Sea Water, Light Blue 3:Ocean, Green	Thermal Shock Resistance:	Resistant

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.