

ARIZONA TILE

FRAGMENT (FRAY) SERIES



Fragment Sand (floor) & Fragment White (wall)



PRODUCT TYPE

Color Body Porcelain
Digital Print Technology

STOCKED COLORS

Fragment Black
Fragment Gray
Fragment Ivory
Fragment Sand
Fragment White

RECOMMENDED USES

Commercial
Residential
Interior Floor
Interior Wall
Exterior Cladding
Fireplaces
Shower Walls
*Shower Floors
Steam Showers
Pool & Spa
* 2 x 2 Mosaic Mesh Only

STOCKED SIZES

12 x 24
2 x 2 Mosaic Mesh

DYNAMIC C.O.F. WET: ≥ 0.42

P.E.I. RATING: 4


FROSTPROOF: Yes

STOCKED TRIM


3 x 12 SBN




Fragment Black




2 x 2 Mosaic Mesh



Fragment Gray




2 x 2 Mosaic Mesh



Fragment Ivory




2 x 2 Mosaic Mesh



Fragment Sand



2 x 2 Mosaic Mesh



Fragment White



2 x 2 Mosaic Mesh

The Fragment (Fray) series is an American-made color body porcelain tile. Using digital print technology, the concept of blending a linen with concrete provides a textural concrete look porcelain surface. Because this material is a porcelain product, minimal maintenance is required. This series is suitable for residential and commercial applications.

There can be noticeable variances between pieces, so it is important and recommended that a range of this product be viewed before finalizing a purchase.

Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color.

For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



For packaging information, please contact your local Arizona Tile.

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Please view actual material when making your selection, as the images on this page are only representative.

Revised 10/14/24

www.arizonatile.com