





ABOVE : RUST POLISHED
COVER: CHARCOAL POLISHED

	Technical Specifications	Standard Requirements	Natural	Polished
	Water Absorption UNI EN ISO 10545-03	E ≤ 0.5%	≤ 0.5%	≤ 0.5%
	Breaking Strength UNI EN ISO 10545-04	≥ 1300 N	≥ 1600 N	≥ 1600 N
	Modulus of Rupture UNI EN ISO 10545-04	> 35 N/mm ²	> 35 N/mm ²	> 35 N/mm ²
	Shock Resistance UNI EN ISO 10545-05	Suggested Minimum: E > 0.55	Resistant	Resistant
	Resistance to Deep Abrasion UNI EN ISO 10545-06	Maximum: 175 mm ³	N/A	N/A
	Thermal Linear Expansion UNI EN ISO 10545-08	As Reported	7.0 x 10 ⁻⁴ /°C	7.0 x 10 ⁻⁴ /°C
	Thermal Shock Resistance UNI EN ISO 10545-09	Required	Resistant	Resistant
	Moisture Expansion UNI EN ISO 10545-10	As Reported	0.1 mm/m	0.1 mm/m
	Frost Resistance UNI EN ISO 10545-12	As Reported	Resistant	Resistant
	Chemical Resistance UNI EN ISO 10545-13	Domestic Chemical Products: UB/ GB Acids and Alkalies: As Reported	Complies with the Standard	Complies with the Standard
	Stain Resistance UNI EN ISO 10545-14	Minimum: Class 3	Class 5	Class 5
PEI	PEI Rating (Scratch Resistance) ASTM C 1027	As Reported	III	III
	Dynamic Coefficient of Friction (DCOF) ANSI A137.1	For Level Interior Spaces Expected to be Walked Upon When wet: ≥ 0.42	< 0.42	N/A
	Shade Variation	As Reported	V3	V3
	Thickness	As Reported	12" x 24" - 9.5 mm 24" x 24" - 9.5 mm 24" x 48" - 10.5 mm	12" x 24" - 9.5 mm 24" x 24" - 9.5 mm 24" x 48" - 10.5 mm
	Number of Screens	As Reported	12" x 24" - 80 24" x 24" - 40 24" x 48" - 20	12" x 24" - 80 24" x 24" - 40 24" x 48" - 20


Grout joint required for rectified edge tile
1/2 broken joint not recommended



MANUFACTURER RECOMMENDS 1/3 OR LESS STAGGERED SPACING



INSTALLATION TIPS



Use a leveling system during installation to reduce lippage



HAPPY FLOORS



≥ 31%



MARBLE



ELECTRIK NATURAL

STATIK

GLAZED RECTIFIED PORCELAIN



BLEND NATURAL

STATIK

Marble is celebrated as the epitome of elegance and purity. In our Statik porcelain collection, classic beauty merges seamlessly with modern allure, highlighted by warm gold veining and captivating blue tones. Explore an array of sizes and finishes, from natural to polished, available in four refined colors tailored to match your unique style. Elevate your space with coordinating hexagonal and 2x2 mosaic tiles, effortlessly infusing your floors and walls with a timeless, graceful ambiance.



ELECTRIK NATURAL

ALL FORMATS AVAILABE IN NATURAL AND POLISHED FINISH

BLEND



12" x 24"
Rectified



24" x 24"
Rectified



24" x 48"
Rectified



Hexagon Mosaic
(10' x 14' Sheet)
Net Coverage: 0.97 sqft



2" x 2" Mosaic
12' x 12' Sheet



3" x 24" Bullnose

RUST



12" x 24"
Rectified



24" x 24"
Rectified



24" x 48"
Rectified



Hexagon Mosaic
(10' x 14' Sheet)
Net Coverage: 0.97 sqft



2" x 2" Mosaic
12' x 12' Sheet



3" x 24" Bullnose



RUST POLISHED

ELECTRIK



12" x 24"
Rectified



24" x 24"
Rectified



24" x 48"
Rectified



Hexagon Mosaic
(10' x 14' Sheet)
Net Coverage: 0.97 sqft



2" x 2" Mosaic
12' x 12' Sheet



3" x 24" Bullnose

CHARCOAL



12" x 24"
Rectified



24" x 24"
Rectified



24" x 48"
Rectified



Hexagon Mosaic
(10' x 14' Sheet)
Net Coverage: 0.97 sqft



2" x 2" Mosaic
12' x 12' Sheet



3" x 24" Bullnose



CHARCOAL POLISHED