


	Technical Specifications	Standard Requirements	Porcelain- Nat.	Ceramic- Glo.
	Water Absorption UNI EN ISO 10545-03	E ≤ 0.5%	< 0.5%	< 3%
	Breaking Strength UNI EN ISO 10545-04	≥ 1300 N	> 1300 N	> 1100 N
	Modulus of Rupture UNI EN ISO 10545-04	> 35 N/mm <sup>2</sup>	> 35 N/mm <sup>2</sup>	> 30 N/mm <sup>2</sup>
	Shock Resistance UNI EN ISO 10545-05	Suggested Minimum: E > 0.55	Resistant	Resistant
	Resistance to Deep Abrasion UNI EN ISO 10545-06	Maximum: 175 mm <sup>3</sup>	N/A	N/A
	Thermal Linear Expansion UNI EN ISO 10545-08	As Reported	6.1 x 10 <sup>-6</sup> /°C <sup>4</sup>	6.1 x 10 <sup>-6</sup> /°C <sup>4</sup>
	Thermal Shock Resistance UNI EN ISO 10545-09	Required	Resistant	Resistant
	Moisture Expansion UNI EN ISO 10545-10	As Reported	≤ 0.01 mm/mm	≤ 0.01 mm/mm
	Frost Resistance UNI EN ISO 10545-12	As Reported	Resistant	Non-Resistant
	Chemical Resistance UNI EN ISO 10545-13	Domestic Chemical Products; UB/GB Acids and Alkalis: As Reported	GLB GLA   GHB	GLB GLA   GHB
	Stain Resistance UNI EN ISO 10545-14	Minimum: Class 3	Class 4	Class 4
	PEI Rating (Scratch Resistance) ASTM C 1027	As Reported	IV	IV
	Dynamic Coefficient of Friction (DCOF) ANSI A137.1	For Level Interior Spaces Expected to be Walked Upon When wet: > 0.42	> 0.42	< 0.42
	Shade Variation	As Reported	V2	V2
	Thickness	As Reported	3" x 12" - 8mm 12" x 24" - 8mm 24" x 24" - 9mm	3" x 12" - 8mm 12" x 24" - 8mm 24" x 24" - 9mm
	Number of Screens	As Reported	3" x 12" - 182 12" x 24" - 26 24" x 24" - 13	3" x 12" - 182 12" x 24" - 26 24" x 24" - 13


Grout joint required for rectified edge tile  
1/2 broken joint not recommended



MANUFACTURER RECOMMENDS 1/3 OR LESS STAGGERED SPACING



INSTALLATION TIPS



Use a leveling system during installation to reduce lippage



MARBLE

# SUBLIME 2.0

WHITE BODY RECTIFIED PORCELAIN & CERAMIC



HAPPY FLOORS



COVER: GRIS 12" x 24"

TOP: DORADO 12" x 24"

**ALL FORMATS AVAILABLE IN  
NATURAL & GLOSSY FINISH**


**GRIS**




**3" x 12"**  
Rectified



**12" x 24"**  
Rectified



**24" x 24"**  
Rectified



**2" x 2" Mosaic**  
**12" x 12" Sheet**  
(Natural Only)



**3" x 24" Bullnose**


**DORADO**



**3" x 12"**  
Rectified



**12" x 24"**  
Rectified



**24" x 24"**  
Rectified



**2" x 2" Mosaic**  
**12" x 12" Sheet**  
(Natural Only)



**3" x 24" Bullnose**



GRIS 12" x 24"



DORADO 12" x 24"

**SUBLIME 2.0**

Sublime's marbled veining comes pronounced just well enough, to give the room an essence of prestige, without overstating itself. This realistic approach to veining keeps harsh lines out of your room, while still giving flair.

Available in both a glossy and a natural finish, Sublime can find itself at home in kitchens, bathrooms, or any other room in the home

GRIS 12" x 24"