

# ARIZONA TILE

# LAGOS SERIES



Lagos Concrete



Lagos Concrete

2 x 2 Mosaic Mesh

4 Inch Hex Mesh



Lagos Ivory

2 x 2 Mosaic Mesh

4 Inch Hex Mesh



Lagos Light Grey

2 x 2 Mosaic Mesh

4 Inch Hex Mesh



Lagos Mud

2 x 2 Mosaic Mesh

4 Inch Hex Mesh



Lagos Sand

2 x 2 Mosaic Mesh

4 Inch Hex Mesh

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



For packaging information, please contact your local Arizona Tile.

*DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.*

Please view actual material when making your selection, as the images on this page are only representative.

Revised 05/03/24

## MADE IN ITALY

### PRODUCT TYPE

Rectified Color Body Porcelain

Digital Print Technology

### STOCKED COLORS

Lagos Concrete

Lagos Ivory

Lagos Light Grey

Lagos Mud

Lagos Sand

### STOCKED SIZES

12 x 24

24 x 48

4 inch Hex Mesh

2 x 2 Mosaic Mesh

### STOCKED TRIM

3 x 12 SBN

### RECOMMENDED USES

Commercial

Residential

Interior Floor

Interior Wall

Exterior Cladding

Fireplaces

Shower Walls

\*Shower Floors

Steam Showers

Pool & Spa

\* 2 x 2 Mosaic Mesh and 4 inch Hex Mesh Only

### SPECIAL ORDER

Special Order Sizes and Finishes Available:  
Please contact your Sales Representative for more details.

**DYNAMIC C.O.F. WET:**  $\geq 0.42$

**P.E.I. RATING:** 4

**FROSTPROOF:** Yes

The Lagos series is an Italian-made rectified color body porcelain. Created using digital print technology, its pattern mimics the look of natural limestone, enhancing its organic appearance. Given the wide selection of color options available in the series, Lagos offers the timeless appeal of natural-stone with the practical properties of porcelain tile. Unlike limestone, minimal maintenance is required. Clean, rectified edges accommodate narrower grout joints thereby giving the illusion of an uninterrupted, honed surface.

Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications. Because this material is a porcelain product, minimal maintenance is required.

For proper bonding, LFT/LHT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.