



Reside Ash USA 24 × 48 R11 Anti-Slip Finish



PRODUCT TYPE

Rectified Color Body Porcelain
Digital Print Technology

STOCKED COLORS

Reside Ash USA
Reside Beige USA
Reside Black USA
Reside Brown USA

STOCKED FINISHES

Matte
R11 Anti-Slip Finish

RECOMMENDED USES

Commercial
Residential
Interior Floor
*Exterior Floor
Interior Wall
Exterior Cladding
Fireplaces
Shower Walls
**Shower Floors
Steam Showers
Pool & Spa
* 24 × 48 R11 Anti-Slip Finish Only
**2 × 2 Mosaic Mesh, Straight Stack 1 × 12 and R11 Anti-Slip Finish Only

DYNAMIC C.O.F. WET: ≥0.42

P.E.I. RATING: 4

FROSTPROOF: Yes

DCOF rating is a measurement of a tile's frictional resistance. The above result is for the Standard Finish. The testing for R11 Anti-Slip Finish is static, which is different from the Dynamic Coefficient of Friction (DCOF) test which is a dynamic test. These two tests measure for different and separate results, therefore the DCOF test is not the appropriate test for the R11 Anti-Slip Finish.



Reside Ash USA



Straight Stack
1 × 12 Mesh



2 × 2 Mosaic Mesh



Reside Beige USA



Straight Stack
1 × 12 Mesh



2 × 2 Mosaic Mesh



Reside Black USA



Straight Stack
1 × 12 Mesh



2 × 2 Mosaic Mesh



Reside Brown USA



Straight Stack
1 × 12 Mesh



2 × 2 Mosaic Mesh

STOCKED SIZES

12 × 24
24 × 24
24 × 48
*24 × 48 R11 Anti-Slip Finish
2 × 2 Mosaic Mesh
Straight Stack 1 × 12 Mesh

STOCKED TRIM

3 × 12 SBN

*Specifically designed for outdoor, exposed areas as well as wet applications, including shower floors. To be certified as R11 Anti-Slip, a tile must pass internationally-recognized testing.

To learn more, visit www.arizonatile.com

The Reside USA Series is a rectified color body porcelain. Inspired by the rich textures of commercial textiles, this series has a clean look and offers a simplistic, modern appeal. It is available in four neutral, on-trend colors and provides an industrial and commercial aesthetic that is available for residential installations as well.

Piece to piece variation in shade or color are inherent in all fired clay products: therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. Because this material is a porcelain product, minimal maintenance is required. This series is suitable for residential and commercial applications.

For proper bonding, LHT/LFT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



For packaging information, please contact your local Arizona Tile.

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Please view actual material when making your selection, as the images on this page are only representative.

Revised 05/03/24