

# Alhambra Series

Deco Tiles



maniscalco

The Alhambra Deco Tiles are expertly crafted to harmonize flawlessly with the aesthetic of the wall tile offering. With two unique designs, these floor patterns provide flexible coordination with any of the four color mixes available in this series. Whether choosing a vibrant or understated palette, these tiles effortlessly elevate the ambiance, infusing a touch of Spanish charm into your design scheme.



*Layla*



Product Sku: AL8X8LY

Color: Layla

Graphic Faces: 20

Sample Card Sku: MSC910-021

*Floor + Wall*





# Alhambra Series

Deco Tiles



*Café Mix*

*Yasmina*

*Yasmina*



Product Sku: AL810YA

Color: Yasmina

Graphic Faces: 6+

Sample Card Sku: MSC910-021

*Tessina*



Product Sku: AL8X8TE

Color: Tessina

Graphic Faces: 6+

Sample Card Sku: MSC910-020



*Crema Mix*

*Tessina*

# Alhambra Series

Deco Tiles



## Technical Data (Deco Tiles):

Standard Norms	Characteristic	Average Values of Production
EN-ISO 10545-2	Dimensional Features	Accomplish/Conform
EN-ISO 10545-3	Water Absorption	> 0.5%
EN-ISO 10545-4	Bending strength	> 35 N/mm <sup>2</sup>
	Breaking strength	> 1300 N
EN ISO 10545-7	Resistance to surface abrasion	Class 4
EN-ISO-10545-9	Thermal shock resistance	Accomplish/Conform
EN ISO 10545-11	Crazing resistance	Accomplish/Conform
EN ISO 10545-12	Frost resistance	Accomplish/Conform
EN ISO 10545-13	Chemical resistance	GHA
EN ISO 10545-14	Resistance to stains	5
UNE-EN-13501-1	Resistance to fire	A1-A1 FL
Friction Coefficient-		
UNE-EN 16165:2022 (C,A)	Pendulum	C3
UNE-EN 16165:2022 (B)	Inclined Platform	R10
ANSI A326.3:2021	DCOF	> 0.42
BS-EN- 16165:2021 (C)	PTV	36+

## Usage (Deco Tiles):

Material	Interior Residential Wall	Interior Residential Floor	Backsplash	Shower Wall	Shower Floor	Fireplace Surround	Exterior Wall	Exterior Floor	Pool	Sealing Required	Color Variation
Porcelain	YES	YES	YES	YES	YES	YES	YES	YES	YES	NO	V2

## Packaging:

PC Size	Sold By	SF Per CTN	PC Per CTN	Weight Per Ctn	Ctn Per Pallet
8" x 8"	CTN	5.60	13	4.25 lb.	87
8" x 10"	CTN	5.60	13	4.60 lb.	96



# Alhambra Series

Undulated Wall Tiles



maniscalco

Introducing Alhambra Series, a captivating collection that redefines elegance in tile design. The undulated wall tiles, each measuring 2-1/2" x 8", present an aesthetic that blends tradition with contemporary sophistication. The series includes a palette of four distinct shades, shaped by our best-selling tile colors. These ink jet printed colors, are meticulously crafted to inspire the allure of the zellige color style. Each variation characterized by a smooth, matte finish that exudes timeless charm. Matching bullnose options are available in the dimensions of 1" x 12". This ensures a cohesive look, providing a finishing touch that complements the overall design scheme.



*Café Mix*

*Café Mix*



Product Sku: AL28CA

Graphic Faces: 6

Sample Card Sku: MSC910-002



Bullnose Sku: AL112CA

*Menta Mix*



Product Sku: AL28ME

Graphic Faces: 8

Sample Card Sku: MSC910-003



Bullnose Sku: AL112ME



*Menta Mix*




# Alhambra Series

Undulated Wall Tiles



maniscalco

*Lago Mix*



Product Sku: AL28LA

Graphic Faces: 7

Sample Card Sku: MSC910-004



Bullnose Sku: AL112LA



*Crema Mix*



*Crema Mix*



Product Sku: AL28CR

Graphic Faces: 6

Sample Card Sku: MSC910-001



Bullnose Sku: AL112CR

# Alhambra Series

Undulated Wall Tiles



maniscalco

## Technical Data (Undulated Tiles):

Standard Norms	Characteristic	Average Values of Production
UNE-EN-ISO 10545-2	Length & Width	+ 0.2%
	Thickness	+ 5.6%
	Surface quality	99% of the tiles are free from visible defects
UNE-EN-ISO 10545-3	Water Absorption	Group Bill > 10%
UNE-EN-ISO 10545-4	Breaking load	345 N
	Modulus of rupture	14 N / mm <sup>2</sup>
	Breaking strength	638 N
EN 101: 1991	Scratch hardness of surface according Mohs	Class 4 (12000 rev)
UNE-EN ISO 10545-7	Resistance to surface abrasion for glazed tiles . PEI method	Class 4 (12000 rev)
UNE-EN ISO 10545-11	Cracking resistance	Resistant. (Tiles tested are free from crazes on the glazed surface)
UNE-EN ISO 10545-13	Resistance to low concentrations of acids and alkalis	GLA Non-visible effects
	Resistance to high concentrations of acids and alkalis	GHA Non-visible effects
	Resistance to domestic products and swimming pool salts	GLA Non-visible effects
UNE-EN ISO 10545-14	Resistance to stains	Class 5

## Usage (Undulated Tiles):

Material	Interior Residential Wall	Interior Residential Floor	Backsplash	Shower Wall	Shower Floor	Fireplace Surround	Exterior Wall	Exterior Floor	Pool	Sealing Required	Color Variation
Ceramic	YES	NO	YES	YES	NO	YES	NO	NO	NO	NO	V3

## Packaging (Undulated Tiles):

PC Size	Sold By	SF Per CTN	PC Per CTN	Weight Per Ctn	Ctn Per Pallet
2-1/2" x 8"	CTN	5.6	40	18.00 lb.	150
1" x 12" (Bullnose)	PC	N/A	57	14.50 lb.	N/A