

ARIZONA TILE

SHIBUSA SERIES



Shibusu Bianco



Straight Stack 1 x 24 Mesh



Shibusu Crema



Straight Stack 1 x 24 Mesh



Shibusu Grigio



Straight Stack 1 x 24 Mesh



Shibusu Tortora



Straight Stack 1 x 24 Mesh



Shibusu Wenge



Straight Stack 1 x 24 Mesh



Hex 9 x 11



Basketweave 2 x 2 Mesh



Long Rhomboid



Long Rhomboid 3 x 4 Mesh



Hex 9 x 11



Basketweave 2 x 2 Mesh



Long Rhomboid



Long Rhomboid 3 x 4 Mesh



Hex 9 x 11



Basketweave 2 x 2 Mesh



Long Rhomboid



Long Rhomboid 3 x 4 Mesh



Hex 9 x 11



Basketweave 2 x 2 Mesh



Long Rhomboid



Long Rhomboid 3 x 4 Mesh



Hex 9 x 11



Basketweave 2 x 2 Mesh



Long Rhomboid



Long Rhomboid 3 x 4 Mesh

MADE IN ITALY

PRODUCT TYPE

Color Body Porcelain
Digital Print Technology

STOCKED COLORS

Shibusu Bianco
Shibusu Crema
Shibusu Grigio
Shibusu Tortora
Shibusu Wenge

STOCKED SIZES

12 x 24 (Rectified)
24 x 48 (Rectified)
Long Rhomboid 3 x 4 Mesh
Hex 9 x 11 (Pressed)
Straight Stack 1 x 24 Mesh
Basketweave 2 x 2 Mesh

STOCKED TRIM

3 x 12 SBN

RECOMMENDED USES

Commercial
Residential
Interior Floor
Interior Wall
Exterior Cladding
Fireplaces
Shower Walls
*Shower Floors
Steam Showers
Pool & Spa

*Basketweave 2 x 2 Mesh, Long Rhomboid 3 x 4 Mesh & Straight Stack 1 x 24 Mesh Only

SPECIAL ORDER

Special Order Sizes, Colors and Finishes
Available: Please contact your Sales Representative for more details.

DYNAMIC C.O.F. WET: ≥0.42

P.E.I. RATING: 4

FROSTPROOF: Yes

The Shibusa Series is a porcelain tile inspired by the rich texture of bamboo. This series has a clean, linear look that offers a simplistic and modern appeal. Because this material is a porcelain product, minimal maintenance is required. It is available in five colors and provides an industrial and commercial aesthetic that is now available for residential installations as well.

Piece to piece variation in shade or color are inherent in all fired clay products; therefore, it is recommended to mix tiles from several boxes at a time during installation to achieve the best range of color. When mixing sizes within a series, shade, texture and calibration differences should be expected. This series is suitable for residential and commercial applications.

For proper bonding, LHT/LFT mortar for large format and heavy tiles should be used when installing tiles with a dimensional length greater than 15 inches, and rectangular shape and plank tile, per industry standards. Proper thinset coverage is also necessary, and in some cases, back buttering of tile may be required.

Minimal chipping on the edge of the tiles is to be expected in mesh mounted products.

When installing rectangular or square tiles 15 inches or longer with a staggered joint, it is recommended that the offset should not exceed 33%, unless otherwise specified by the manufacturer.



For packaging information, please contact your local Arizona Tile.

DCOF rating is a measurement of a tile's frictional resistance. It is the specifier's responsibility to ensure the chosen tile is appropriate for each interior and exterior application.

Please view actual material when making your selection, as the images on this page are only representative.

Revised 03/25/25

www.arizonatile.com