NEW PRODUCT SERIES

Technical Information Spec-sheet

International Wholesale Tile, LLC

SERIES NAME	**Industrial**

TECHNICAL CHARACTERISTICS			
Available Formats:	6.25x15.25		
Style Description:	Decorative Wall	Glaze Application Method:	Inkjet
Thickness in mm:	8-10 mm	Number of Faces/Screens:	14
Application:	Residential, Commercial, Floor, Exterior Wall Only.	Number of Punches/Molds:	1
Rectified or Pressed:	Pressed	Body Type:	Gres Porcelain
Recycled Content: Post or Pre Customer	5.43 %	Surface Type:	Matte
Recommended Grout:	Mapei 5093 Warm Gray Ultracolor Plus FA Grout	Recommended Grout Joint:	No joint

PRODUCT TESTING INFORMATION			
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)			
Water Absorption:	0.2%	Chemical Resistance:	GLA/GHA/GA
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	N/A
Frost Resistant:	Yes	Breaking Strength:	55.7 N/mm2
PEI/Abrasion Resistance:	V, R10	Thermal Shock Resistance:	N/A

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.

3500 SW 42nd Avenue | Palm City, FL 34990 | T: 800-340-TILE (8453) | F: 888-765-TILE (8453)
info@iwttesoro.com | www.iwttesoro.com