

MARRAKESH

CERAMIC WALL TILES





MARRAKESH

CERAMIC WALL TILES

MARRAKESH OFF WHITE



15x15 cm | 6"x6"
BR (GLOSSY)

MARRAKESH BLUE



15x15 cm | 6"x6"
BR (GLOSSY)

MARRAKESH GREEN



15x15 cm | 6"x6"
BR (GLOSSY)



WALLS



FIRE PROOF



VOC FREE



MARRAKESH

CERAMIC WALL TILES

PRODUCT INFORMATION

	Type / Size	Series	Finish	Rectified	Unit	Work Size (mm)	Thick	Faces	Sq. Ft. / Carton	Pieces / Carton
	Wall Tiles 6"x6"	MARRAKESH	Glossy	No	SF	154x154	7 mm	40	13.90	54

USAGE RECOMMENDATION

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	
Wet & Level - Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes - Interior	N/A	✓
Countertops	N/A	
Facades	N/A	
Pool Linings	N/A	

QUALITY WARRANTY

	Meet or exceed ISO 13006, NBR 15463 and NBR 13818, ANSI A137.1 standards.		Our ceramic and porcelain tiles are NOT flammable, except mesh material of mesh mounted mosaics.
	Our ceramic and porcelain tiles are low-emitting materials with zero emission of volatile organic compounds (VOC).		

INSTALLATION AND CARE

Grout Joint Recommendation 1/16"
Shade Variation  V3 - MODERATE VARIATION

Professional tile installation is recommended. For complete installation instructions consult the TCNA Handbook for Ceramic, Glass, and Stone Tile Installation. Follow the grout manufacturer instructions for the complete removal of grout and construction residue from initial installation.

Eliane's recommendation for flooring care: sweep or vacuum the surface. Then mop the floor using a mop with water and a neutral cleaner (soap less) or a general household cleaner. Follow it with a clean water rinsed mop and wipe dry the floor to prevent film formation. For wall tiles care, Eliane recommends using a cloth with water and a neutral cleaner (soap less) or a general household cleaner.

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	≤ 20%
Breaking Strength	C648	≥ 125 lbs
DCOF WET	ANSI A137.1 ANSI A326.3	N/A
Scratch Hardness	MOHS	4
Frost Resistance	C1026	No
Chemical Resistance	C650	Class A
Stain Resistance	C1378	Class A



