















TACOMA				
	Technical Specifications	Reference Standard	Standard Requirements	Test Results
	Water Absorption	UNI EN ISO 10545-03	< 0.5 %	In Accordance
	Breaking Strength	UNI EN ISO 10545-04	Minimum: 1300 N	In Accordance
	Modulus of Rupture	UNI EN ISO 10545-04	Minimum: 35 N/mm²	In Accordance
	Shock Resistance	UNI EN ISO 10545-05	Suggested Minimum: e > 0.55	Resistant
	Resistance to Deep Abrasion	UNI EN ISO 10545-06	Maximum: 175 mm³	In Accordance
	Thermal Shock Resistance	UNI EN ISO 10545-09	Resistant	In Accordance
	Frost Resistance	UNI EN ISO 10545-12	As Reported	Resistant
	Chemical Resistance	UNI EN ISO 10545-13	Domestic Chemical Products: UB / GB Acids and Alkalies: As Reported	In Accordance
	Stain Resistance	UNI EN ISO 10545-14	Minimum: Class 3	In Accordance
PEI	PEI Rating (Scratch Resistance)	ASTM C 1027	As Reported	V: Crest IV: Valley I Summer I Shadow
DCOF	Dynamic Coefficient of Friction (DCOF)	ANSI A137.1	For Level Interior Spaces Expected to be Walked Upon When Wet : > 0.42	0.67
V2	Shade Variation	Not Available	As Reported	V2
	Thickness	Not Available	As Reported	10 mm
	Number of Screens	Not Available	As Reported	18



HAPPY FLOORS
WWW.HAPPY-FLOORS.COM

I-Design
Collection

DIGITAL INKJET TILE
HD

M A D E I N
I T A L Y





CREST



SUMMER

VALLEY



6"X40"



BULLNOSE 3"X20"

SUMMER



6"X40"



BULLNOSE 3"X20"

CREST



6"X40"



BULLNOSE 3"X20"

SHADOW



6"X40"



BULLNOSE 3"X20"